




**HANYU CABLE MATERIALS CO., LTD.**

## Film Laminated Water blocking Tapes, NCWF

**Composition:** Polyester non-woven fabric, polyester film, super absorbent resin, adhesive.

**Application:** Be used for water-blocking in neutral screen wire between cable components.



## Technical Data

Property	Unit	Types	Test Method
		NCWF-25	
Thickness	mm	0.25±0.03	ISO9073-2
Mass per unit area	g/m <sup>2</sup>	110±10	ISO9073-1
Tensile strength	N/cm	≥45	ISO9073-3
Elongation	%	≥12	ISO9073-3
Swelling speed	mm/1'00	≥8	HYtest-10
Swelling height	mm/3'00	≥12	HYtest-11
Short-term stability	°C	230	HYtest-5
Long-term stability	°C	90	IEC216
Moisture content	%	<9	ISO287

These are general specifications, other specifications are available on request.  
 Spool is ordered from 150mm-700mm. Width, ID are also available on request.  
 Package: plastic foil bag inside, carton and pallet.

Add: No. 666 West Yangting Road, Weihai, Shandong, China [Http://www.cnhanyu.com](http://www.cnhanyu.com)  
 Tel: +86 631 576 9996 Fax: +86 631 576 4088